

Product Data


4DCY4024 through 4DCY4060

Single Packaged Convertible Dual Fuel

14 SEER

2 - 5 Ton, 40 - 120 MBTU

R-410A



Built to A Higher Standard.

Single Packaged Convertible Dual Fuel System

American Standard Heating & Air Conditioning offers a complete family of dual fuel heating and cooling systems, designed to keep you comfortable all year long, regardless of the weather, while keeping your operating costs as low as possible. The heat pump operates efficiently as both an air conditioner and a heater. In the summer, the heat pump cools your home just like any other air conditioner by pulling the heat from the inside and releasing it outdoors. In the winter, it captures the heat that is always present in the outdoor air and transfers it indoors. The gas furnace provides additional heating capacity for cooler weather.

Introducing the new American Standard Heating & Air Conditioning Single Packaged Convertible Dual Fuel System.

Single Packaged Convertible Dual Fuel Systems are easy and versatile to install. Because cooling and heating functions are all contained in a single cabinet, an American Standard Heating & Air Conditioning packaged dual fuel system is easy to install and service. It can be flush mounted beside your home at ground level or placed on the roof for horizontal or downflow installation. When connected to a *CONT402, 802, or 803 comfort control, and air distribution ducts, you have a highly efficient, total home comfort system.

Single Packaged Dual Fuel Systems are unmatched in quality and reliability. All major components on these products, including the compressor, have been designed and manufactured for maximum service. Every Duration™ compressor is designed and manufactured to exacting specifications. Each design is life tested in extreme environments to ensure reliable and long lasting operation in normal applications. Each compressor has internal motor protection for added reliability.

Contents

Optional Equipment Listing	4
General Data	5
Performance Data	
Cooling	8
Heating	10
Indoor Blower Performance	12
Typical Wiring	15
Optional Equipment	18
Dimensional Data	23
Mechanical Specifications	29

Optional Equipment Listing

OPTIONAL EQUIPMENT FOR 4DCY4 PACKAGED UNITS (check mark [✓] indicates accessories included)

Hinged Filter Access Door (4DCY4024-036) ⑧	BAYACCDOR1A[]
Hinged Filter Access Door (4DCY4042-060) ⑧	BAYACCDOR2A[]
Roof Curb Full Perimeter (4DCY4024-036A) ③	BAYCURB050A[]
Roof Curb Full Perimeter (4DCY4042-060A) ③	BAYCURB051A[]
Roof Curb Utility Extension Kit (BAYCURB050A)	BAYUTIL101B[]
Roof Curb Utility Extension Kit (BAYCURB051A)	BAYUTIL102B[]
0-25% Manual Fresh Air Damper (4DCY4024-36A) ①	BAYOSAH001A[]
0-25% Manual Fresh Air Damper (4DCY4042-060A) ①	BAYOSAH002A[]
Motorized Fresh Air Damper (4DCY4024-36A) ①	BAYDMPR101A[]
Motorized Fresh Air Damper (4DCY4042-060A) ①	BAYDMPR102A[]
16" Round Duct Adapter (2 per box) (4DCY4024-36A) ⑥	BAYSQRD001A[]
18" Round Duct Adapter (2 per box) (4DCY4024-060A) ⑥	BAYSQRD002A[]
0-100% Mod Economizer w/Baro. Relief (4DCY4024-36A) ①②④	BAYECON101B[]
0-100% Mod. Economizer w/Baro. Relief (4DCY4042-060A) ①②④	BAYECON102B[]
0-100% Horizontal Economizer (4DCY4024-36A) ①②	BAYECON200A[]
0-100% Horizontal Economizer (4DCY4042-060A) ①②	BAYECON201A[]
Economizer Relay Kit (required for Heat Pump applications)	BAYRLAY004A[]
Enthalpy Control for Economizer (solid state)	BAYENTH001A[]
Remote Potentiometer (All-BAYECON***A)	BAYSTAT023[]
1"-2" Filter Frame (4DCY4024-36A) (20 x 25 filter not included) ①	BAYFLTR101B[]
1"-2" Filter Frame (4DCY4042A) (20 x 20 & 20 x 18 filter not included) ①	BAYFLTR201B[]
Head Pressure Control (Low Ambient Cool) (208/240v) Kit ⑤	BAYLOAM105A[]
Quick Start Kit (4DCY4-A1)	BAYQSKT300A[]
Crankcase Heater Recip (4DCY4024A1 (230v) ⑤	BAYCCHT101A[]
Crankcase Heater Scroll(4DCY4036,48, 60A1/3)(230v) ⑤	BAYCCHT102A[]
Adapter Curb 4DCY4024-36A to BAYCURB030,38	BAYADAP050A[]
Adapter Curb 4DCY4024-36A to BAYCURB033	BAYADAP051A[]
Adapter Curb 4DCY4042-60A to BAYCURB030,38	BAYADAP052A[]
Adapter Curb 4DCY4042-60A to BAYCURB033	BAYADAP053A[]
Adapter Curb 4DCY4042-60A to BAYCURB034	BAYADAP054A[]
12" Duct Shroud Covers Horizontal *DCY4024-60A ⑦	BAYCOVR112A[]
18" Duct Shroud Covers Horizontal *DCY4024-60A ⑦	BAYCOVR118A[]
Extreme Condition Mounting Kit - All BAYCURB & BAYADAP	BAYEXMK001A[]
Extreme Condition Mounting Kit - All BAYUTIL	BAYEXMK002B[]
Extreme Condition Mounting Kit - All Slab Mounts	BAYEXMK003A[]
Lifting Lug Kit	BAYLIFT002B[]
LP Conversion Kit (All 40K, 120K Models)	BAYLPKT100A[]
LP Conversion Kit (All 64K, 96K Models)	BAYLPKT101A[]
LP Conversion Kit (All 75K Models)	BAYLPKT102A[]

- NOTES: ① Must use internal filter frame when economizer or fresh air kit is used.
 ② Dry bulb control standard with economizer.
 ③ Ships knocked down.
 ④ Downflow only.
 ⑤ Low Ambient cooling requires crankcase heater (BAYCCHT----A).
 ⑥ It is the responsibility of the installing dealer to properly size the ductwork for each specific application.
 ⑦ BAYCOVR112,118A will not cover BAYSQRD002A applications.
 ⑧ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.

General Data

MODEL	4DCY4024A1064A	4DCY4030A1075A	4DCY4036A1075A
RATED Volts/PH/Hz	208-230/1/60	208-230/1/60	208-230/1/60
Performance Cooling BTUH®	23600	30000	36000
Indoor Airflow (CFM)	760	880	1185
Power Input (KW)	2.162	2.15	3.284
EER/SEER(BTU/Watt-Hr.)⑤	12/14.0	12.0 / 14.25	11.4 / 14.0
Sound Power Rating [dB(A)]⑦	68	71	69
HP Heating Performance			
(High Temp.)BTUH / COP	22400 / 3.7	28000 / 3.9	34600 / 3.5
Power Input (KW)	1.77	2.15	2.8
(Low Temp.) BTUH / COP	11600 / 2.38	15400 / 2.48	20600 / 2.36
Power Input (KW)	1.24	1.81	2.6
HSPF (BTU / Watt-Hr.)	8.0	8.0	8.0
Gas Heating Performance②			
(High) Input BTUH	64000	75000	75000
Capacity BTUH	51500	60500	60500
Temp. Rise — Min/Max (°F)	35 / 65	30 / 60	30 / 60
(Low) Input BTUH	48000	56250	56250
Capacity BTUH	41200	48400	48400
AFUE	79	79.5	79.5
Type of Gas ③	NATURAL	NATURAL/LP	NATURAL
Gas Pipe Size (in.)	1/2	1/2	1/2
POWER CONN.—V/PH/HZ	208-230/1/60	208-230/1/60	208-230/1/60
Min. Brch. Cir. Ampacity④	16.1	19.1	24.6
Fuse Size — Max. (amps)	25	30	40
Fuse Size — Recmd. (amps)	25	30	40
COMPRESSOR	RECIPROCATING	RECIPROCATING	SCROLL
Volts/Ph/Hz	208-230/1/60	200-230/1/60	208-230/1/60
R.L. Amps — L.R. Amps	8.3 / 57.8	11.1 / 63	15.4 / 83
OUTDOOR COIL — TYPE	SPINE-FIN	SPINE-FIN	SPINE-FIN
Rows/F.P.I.	2 / 24	2 / 24	2 / 24
Face Area (sq.ft.)	13.32	13.32	15.49
Tube Size (in.)	3/8	3/8	3/8
Refrigerant Control	EXPANSION VALVE	EXPANSION VALVE	EXPANSION VALVE
INDOOR COIL — TYPE	PLATE FIN	PLATE FIN	PLATE FIN
Rows/F.P.I.	3 / 15	4 / 15	4 / 15
Face Area (sq.ft.)	3.54	3.54	3.54
Tube Size (in.)	3/8	3/8	3/8
Refrigerant Control	EXPANSION VALVE	EXPANSION VALVE	EXPANSION VALVE
Drain Conn. Size (in.)	3/4 FEMALE NPT	3/4 FEMALE NPT	3/4 FEMALE NPT
OUTDOOR FAN — TYPE	PROPELLER	PROPELLER	PROPELLER
Dia. (in.)	23.4	23.4	23.4
Drive/No. Speeds	DIRECT / 1	DIRECT / 1	DIRECT / 1
CFM @ 0.0 in. w.g. ⑦	2590	3250	3270
Motor — HP/R.P.M.	1/12 / 810	1/6 / 830	1/5 / 830
Volts/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60
F.L. Amps/L.R. Amps	0.54 / 0.95	1.0 / 1.7	1.1 / 1.9
INDOOR FAN — TYPE	CENTRIFUGAL	CENTRIFUGAL	CENTRIFUGAL
Dia x Width (in.)	10 X 10	10 X 10	10 X 10
Drive/No. Speeds	DIRECT / VARIABLE	DIRECT / VARIABLE	DIRECT / VARIABLE
CFM @ 0.0 in. w.g.⑤	SEE FAN PERFORMANCE TABLE	SEE FAN PERFORMANCE TABLE	SEE FAN PERFORMANCE TABLE
Motor — HP/R.P.M.	1/2 / VARIABLE	1/2 / VARIABLE	1/2 / VARIABLE
Volts/Ph/Hz	200-230/1/60	208-230/1/60	200-230/1/60
F.L. Amps/L.R. Amps	4.3 / 4.3	4.3 / 4.3	4.3 / 4.3
COMBUSTION FAN — TYPE	CENTRIFUGAL	CENTRIFUGAL	CENTRIFUGAL
Drive/No. Speeds	DIRECT / 2	DIRECT / 2	DIRECT / 2
Motor — HP/R.P.M. (High/Low)	1/45 / 2800/1500	1/45 / 2800/1500	1/45 / 2800/1500
Volts/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60
FLA	0.34	0.34	0.34
FILTER / FURNISHED	NO	NO	NO
Type Recommended	THROWAWAY	THROWAWAY	THROWAWAY
Recmd. Face Area (sq. ft.)⑥	4	4	4
REFRIGERANT / Charge (lbs.)	R410A / 6.5	R410A / 6.56	R410A / 7.4
DIMENSIONS	H X W X L	H X W X L	H X W X L
Crated (in.)	45.86 / 44.5 / 52.03	45.86 / 44.5 / 52.03	47.86 / 44.5 / 52.03
WEIGHT / Shipping / Net (lbs.)	481 / 385	481 / 385	488 / 392

① Certified in accordance with the Unitary Air-Conditioner Equipment certification program, which is based on ARI Standard 210/240.

② All models are U L Listed. Ratings shown are for elevations up to 2000 ft. For higher elevations reduce ratings at a rate of 4% per 1000 ft. elevation.

③ Convertible to LPG.

④ This value is approximate. For more precise value, see Unit Nameplate.

⑤ Based on U.S. Government Standard Tests.

⑥ Filters must be installed in return air stream. Square footages listed are based on 300 f.p.m. face velocity. If permanent filters are used size per manufacturer's recommendation with a clean resistance of 0.05" W.C.

⑦ Sound Power values are not adjusted for ARI 270-95 tonal corrections.

⑧ Standard Air — Dry Coil — Outdoor.

Pub. No. 12-1254-08

General Data

MODEL	4DCY4036A3075A	4DCY4042A1096A	4DCY4048A1096A
RATED Volts/PH/Hz	208-230/3/60	208-230/1/60	208-230/1/60
Performance Cooling BTUH^①	36000	42000	47000
Indoor Airflow (CFM)	1185	1370	1470
Power Input (KW)	3.284	3.27	4.034
EER/SEER(BTU/Watt-Hr.) ^⑤	11.4 / 14.0	12.0 / 14.25	11.75 / 14.0
Sound Power Rating [dB(A)] ^⑦	69	74	73
HP Heating Performance			
(High Temp.) BTUH / COP	34600 / 3.5	39500 / 3.6	45500 / 3.5
Power Input (KW)	2.8	3.27	3.74
(Low Temp.) BTUH / COP	20600 / 2.36	23600 / 2.26	26800 / 2.3
Power Input (KW)	2.6	3.06	3.44
HSPF (BTU / Watt-Hr.)	8.0	8.0	8.0
Gas Heating Performance^②			
(High) Input BTUH	75000	96000	96000
Capacity BTUH	60500	77500	77500
Temp. Rise — Min/Max (°F)	30 / 60	30 / 60	30 / 60
(Low) Input BTUH	56250	72000	72000
Capacity BTUH	48400	62000	62000
AFUE	80.0	80	80
Type of Gas ^③	NATURAL	NATURAL/LP	NATURAL
Gas Pipe Size (in.)	1/2	1/2	1/2
POWER CONN.—V/PH/Hz	208-230/3/60	208-230/1/60	208-230/1/60
Min. Brch. Cir. Ampacity ^④	19.8	31.5	33.9
Fuse Size — Max. (amps)	30	50	50
Fuse Size — Recmd. (amps)	30	50	50
COMPRESSOR	SCROLL	SCROLL	SCROLL
Volts/Ph/Hz	208-230/3/60	208-230/1/60	208-230/1/60
R.L. Amps — L.R. Amps	11.5 / 77	18.6 / 105	20.5 / 109
OUTDOOR COIL — TYPE	SPINE-FIN	SPINE-FIN	SPINE-FIN
Rows/F.P.I.	2 / 24	2 / 24	2 / 24
Face Area (sq.ft.)	15.49	18.01	18.01
Tube Size (in.)	3/8	3/8	3/8
Refrigerant Control	EXPANSION VALVE	EXPANSION VALVE	EXPANSION VALVE
INDOOR COIL — TYPE	PLATE FIN	PLATE FIN	PLATE FIN
Rows/F.P.I.	4 / 15	3 / 15	3 / 15
Face Area (sq.ft.)	3.54	5	5.0
Tube Size (in.)	3/8	3/8	3/8
Refrigerant Control	EXPANSION VALVE	EXPANSION VALVE	EXPANSION VALVE
Drain Conn. Size (in.)	3/4 FEMALE NPT	3/4 FEMALE NPT	3/4 FEMALE NPT
OUTDOOR FAN — TYPE	PROPELLER	PROPELLER	PROPELLER
Dia. (in.)	23.4	28.2	28.2
Drive/No. Speeds	DIRECT / 1	DIRECT / 1	DIRECT / 1
CFM @ 0.0 in. w.g. ^⑥	3270	4440	4450
Motor — HP/R.P.M.	1/5 / 830	1/4 / 825	1/4 / 825
Volts/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60
F.L. Amps/L.R. Amps	1.1 / 1.9	1.5 / 3.4	1.4 / 3.5
INDOOR FAN — TYPE	CENTRIFUGAL	CENTRIFUGAL	CENTRIFUGAL
Dia x Width (in.)	10 X 10	11 X 10	11 X 10
Drive/No. Speeds	DIRECT / VARIABLE	DIRECT / VARIABLE	DIRECT / VARIABLE
CFM @ 0.0 in. w.g. ^⑥	SEE FAN PERFORMANCE TABLE	SEE FAN PERFORMANCE TABLE	SEE FAN PERFORMANCE TABLE
Motor — HP/R.P.M.	1/2 / VARIABLE	3/4 / VARIABLE	3/4 / VARIABLE
Volts/Ph/Hz	200-230/1/60	208-230/1/60	200-230/1/60
F.L. Amps/L.R. Amps	4.3 / 4.3	6.8 / 6.8	6.8 / 6.8
COMBUSTION FAN — TYPE	CENTRIFUGAL	CENTRIFUGAL	CENTRIFUGAL
Drive/No. Speeds	DIRECT / 2	DIRECT / 2	DIRECT / 2
Motor — HP/R.P.M. (High/Low)	1/45 / 2800/1500	1/45 / 2800/1500	1/45 / 2800/1500
Volts/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60
FLA	0.34	0.34	0.34
FILTER / FURNISHED	NO	NO	NO
Type Recommended	THROWAWAY	THROWAWAY	THROWAWAY
Recmd. Face Area (sq. ft.) ^⑧	4	5.3	5.3
REFRIGERANT / Charge (lbs.)	R410A / 7.4	R410A / 7.25	R410A / 7.75
DIMENSIONS	H X W X L	H X W X L	H X W X L
Crated (in.)	47.86 / 44.5 / 52.03	47.86 / 47.4 / 61.75	47.86 / 47.4 / 61.75
WEIGHT / Shipping / Net (lbs.)	488 / 392	653 / 525	653 / 525

① Certified in accordance with the Unitary Air-Conditioner Equipment certification program, which is based on ARI Standard 210/240.

② All models are U L Listed. Ratings shown are for elevations up to 2000 ft. For higher elevations reduce ratings at a rate of 4% per 1000 ft. elevation.

③ Convertible to LPG.

④ This value is approximate. For more precise value, see Unit Nameplate.

⑤ Based on U.S. Government Standard Tests.

⑥ Filters must be installed in return air stream. Square footages listed are based on 300 f.p.m. face velocity. If permanent filters are used size per manufacturer's recommendation with a clean resistance of 0.05" W.C.

⑦ Sound Power values are not adjusted for ARI 270-95 tonal corrections.

⑧ Standard Air — Dry Coil — Outdoor.

General Data

MODEL	4DCY4048A3096A	4DCY4060A1120A	4DCY4060A3120A
RATED Volts/PH/Hz	208-230/3/60	208-230/1/60	208-230/3/60
Performance Cooling BTUH®	47000	57500	57500
Indoor Airflow (CFM)	1470	1745	1745
Power Input (KW)	4.034	5.478	5.478
EER/SEER(BTU/Watt-Hr.) ^⑤	11.75 / 14.0	11.5 / 14.0	11.5 / 14.0
Sound Power Rating [dB(A)] ^⑦	73	76	76
HP Heating Performance			
(High Temp.) BTUH / COP	45500 / 3.5	57000 / 3.5	57000 / 3.5
Power Input (KW)	3.74	4.43	4.43
(Low Temp.) BTUH / COP	26800 / 2.3	36400 / 2.48	36400 / 2.48
Power Input (KW)	3.44	4.29	4.29
HSPF (BTU / Watt-Hr.)	8.0	8.0	8.0
Gas Heating Performance®			
(High) Input BTUH	96000	120000	120000
Capacity BTUH	77500	96000	96000
Temp. Rise — Min/Max (°F)	30 / 60	30 / 60	30 / 60
(Low) Input BTUH	72000	90000	90000
Capacity BTUH	62000	77500	77500
AFUE	80	80.0	80.0
Type of Gas ^③	NATURAL	NATURAL	NATURAL
Gas Pipe Size (in.)	1/2	1/2	1/2
POWER CONN.—V/PH/HZ	208-230/3/60	208-230/1/60	208-230/3/60
Min. Brch. Cir. Ampacity ^④	26.4	42.3	30.6
Fuse Size — Max. (amps)	40	60	60
Fuse Size — Recmd. (amps)	40	60	60
COMPRESSOR	SCROLL	SCROLL	SCROLL
Volts/Ph/Hz	208-230/3/60	208-230/1/60	208-230/3/60
R.L. Amps — L.R. Amps	14.6 / 91	26.9 / 145	26.9 / 145
OUTDOOR COIL — TYPE	SPINE-FIN	SPINE-FIN	SPINE-FIN
Rows/F.P.I.	2 / 24	2 / 24	2 / 24
Face Area (sq.ft.)	18.01	23.57	23.57
Tube Size (in.)	3/8	3/8	3/8
Refrigerant Control	EXPANSION VALVE	EXPANSION VALVE	EXPANSION VALVE
INDOOR COIL — TYPE	PLATE FIN	PLATE FIN	PLATE FIN
Rows/F.P.I.	3 / 15	4 / 15	4 / 15
Face Area (sq.ft.)	5.0	5.0	5.0
Tube Size (in.)	3/8	3/8	3/8
Refrigerant Control	EXPANSION VALVE	EXPANSION VALVE	EXPANSION VALVE
Drain Conn. Size (in.)	3/4 FEMALE NPT	3/4 FEMALE NPT	3/4 FEMALE NPT
OUTDOOR FAN — TYPE	PROPELLER	PROPELLER	PROPELLER
Dia. (in.)	28.2	28.2	28.2
Drive/No. Speeds	DIRECT / 1	DIRECT / 1	DIRECT / 1
CFM @ 0.0 in. w.g. ^⑦	4450	5710	5710
Motor — HP/R.P.M.	1/4 / 825	1/3 / 830	1/3 / 830
Volts/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60
F.L. Amps/L.R. Amps	1.4 / 3.5	1.7 / 3.5	1.7 / 3.5
INDOOR FAN — TYPE	CENTRIFUGAL	CENTRIFUGAL	CENTRIFUGAL
Dia x Width (in.)	11 X 10	11 X 10	11 X 10
Drive/No. Speeds	DIRECT / VARIABLE	DIRECT / VARIABLE	DIRECT / VARIABLE
CFM @ 0.0 in. w.g. ^⑤	SEE FAN PERFORMANCE TABLE	SEE FAN PERFORMANCE TABLE	SEE FAN PERFORMANCE TABLE
Motor — HP/R.P.M.	3/4 / VARIABLE	1 / VARIABLE	1 / VARIABLE
Volts/Ph/Hz	200-230/1/60	208-230/1/60	208-230/1/60
F.L. Amps/L.R. Amps	6.8 / 6.8	6.9 / 6.9	6.9 / 6.9
COMBUSTION FAN — TYPE	CENTRIFUGAL	CENTRIFUGAL	CENTRIFUGAL
Drive/No. Speeds	DIRECT / 2	DIRECT / 2	DIRECT / 2
Motor — HP/R.P.M. (High/Low)	1/45 / 2800/1500	1/45 / 2800/1500	1/45 / 2800/1500
Volts/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60
FLA	0.34	0.34	0.34
FILTER / FURNISHED	NO	NO	NO
Type Recommended	THROWAWAY	THROWAWAY	THROWAWAY
Recmd. Face Area (sq. ft.) ^⑥	5.3	6.7	6.7
REFRIGERANT / Charge (lbs.)	R410A / 7.75	R410A / 10.125	R410A / 10.125
DIMENSIONS	H X W X L	H X W X L	H X W X L
Crated (in.)	47.86 / 47.4 / 61.75	51.86 / 47.4 / 61.75	51.86 / 47.4 / 61.75
WEIGHT / Shipping / Net (lbs.)	653 / 525	676 / 548	676 / 548

① Certified in accordance with the Unitary Air-Conditioner Equipment certification program, which is based on ARI Standard 210/240.

② All models are U L Listed. Ratings shown are for elevations up to 2000 ft. For higher elevations reduce ratings at a rate of 4% per 1000 ft. elevation.

③ Convertible to LPG.

④ This value is approximate. For more precise value, see Unit Nameplate.

⑤ Based on U.S. Government Standard Tests.

⑥ Filters must be installed in return air stream. Square footages listed are based on 300 f.p.m. face velocity. If permanent filters are used size per manufacturer's recommendation with a clean resistance of 0.05" W.C.

⑦ Sound Power values are not adjusted for ARI 270-95 tonal corrections.

⑧ Standard Air — Dry Coil — Outdoor.

Pub. No. 12-1254-08

Performance Data Cooling

4DCY4024A1 AT 800 NOM CFM (COOLING PERFORMANCE AT INDOOR DRY BULB TEMPERATURES)

OD AMB	ID WB	TOT CAP	SENS CAP AT ENTERING DB TEMP				TOTAL KW
			72	75	78	80	
85	59	23.3	19.4	21.8	23.3	23.3	1.8
	63	24.3	15.8	18.2	20.6	22.1	1.8
	67	26.2	12.6	14.9	17.3	18.9	1.9
	71	28.2	9.3	11.7	14.0	15.6	1.9
95	59	21.2	18.5	20.8	21.2	21.2	2.0
	63	22.1	15.0	17.3	19.7	21.2	2.0
	67	23.8	11.7	14.1	16.4	18.0	2.0
	71	25.7	8.4	10.8	13.2	14.7	2.0
105	59	19.2	17.6	19.2	19.2	19.2	2.1
	63	20.0	14.1	16.4	18.8	20.0	2.1
	67	21.5	10.8	13.2	15.6	17.1	2.2
	71	23.2	7.6	10.0	12.3	13.9	2.2
115	59	17.1	16.7	17.1	17.1	17.1	2.3
	63	17.8	13.2	15.6	17.8	17.8	2.3
	67	19.2	10.0	12.4	14.7	16.3	2.3
	71	20.7	6.8	9.1	11.5	13.1	2.3

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	700	0.97	0.98
HIGH	900	1.03	1.02

ARI RATING FOR COOLING			
CFM	CAPACITY (A) TEST	SEER	EER
758	23600	14.00	11.80

ARI Standard Capacity Rating Conditions
 ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4030A1 AT 1000 NOM CFM (COOLING PERFORMANCE AT INDOOR DRY BULB TEMPERATURES)

OD AMB	ID WB	TOT CAP	SENS CAP AT ENTERING DB TEMP				TOTAL KW
			72	75	78	80	
85	59	29.8	24.6	27.6	29.8	29.7	2.3
	63	31.1	20.1	23.1	26.0	28.1	2.3
	67	33.5	16.0	19.0	21.9	23.9	2.3
	71	36.2	11.8	14.8	17.8	19.8	2.3
95	59	27.4	23.5	26.5	27.4	27.4	2.5
	63	28.5	19.0	22.0	25.0	27.0	2.5
	67	30.7	14.9	17.9	20.9	22.8	2.5
	71	33.2	10.8	13.8	16.7	18.7	2.5
105	59	24.9	22.4	24.9	24.9	24.9	2.7
	63	25.9	18.0	21.0	23.9	25.9	2.7
	67	27.9	13.9	16.9	19.8	21.8	2.7
	71	30.2	9.8	12.7	15.7	17.7	2.7
115	59	22.4	21.3	22.4	22.4	22.4	2.9
	63	23.3	16.9	19.9	22.9	23.3	2.9
	67	25.2	12.9	15.8	18.8	20.8	2.9
	71	27.2	8.7	11.7	14.7	16.7	2.9

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	875	0.97	0.98
HIGH	1125	1.03	1.02

ARI RATING FOR COOLING			
CFM	CAPACITY (A) TEST	SEER	EER
880	30000	14.25	12.00

ARI Standard Capacity Rating Conditions
 ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4036A1/3 AT 1200 NOM CFM (COOLING PERFORMANCE AT INDOOR DRY BULB TEMPERATURES)

OD AMB	ID WB	TOT CAP	SENS CAP AT ENTERING DB TEMP				TOTAL KW
			72	75	78	80	
85	59	34.4	29.0	32.6	34.4	34.4	2.8
	63	35.9	23.5	27.1	30.8	33.2	2.8
	67	38.7	18.5	22.1	25.8	28.2	2.8
	71	41.7	13.5	17.1	20.7	23.1	2.8
95	59	32.1	27.9	31.6	32.1	32.1	3.1
	63	33.5	22.5	26.1	29.8	32.2	3.1
	67	36.1	17.5	21.1	24.8	27.2	3.2
	71	38.9	12.5	16.1	19.8	22.2	3.2
105	59	29.8	26.9	29.8	29.8	29.8	3.4
	63	31.1	21.6	25.2	28.8	31.1	3.4
	67	33.5	16.5	20.2	23.8	26.2	3.5
	71	36.2	11.6	15.2	18.8	21.2	3.5
115	59	27.5	25.9	27.5	27.5	27.5	3.7
	63	28.7	20.6	24.2	27.8	28.7	3.8
	67	30.9	15.6	19.2	22.9	25.3	3.8
	71	33.4	10.6	14.3	17.8	20.3	3.8

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1050	0.97	0.98
HIGH	1350	1.03	1.02

ARI RATING FOR COOLING			
CFM	CAPACITY (A) TEST	SEER	EER
1187	36000	14.00	11.40

ARI Standard Capacity Rating Conditions
 ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

Performance Data Cooling

4DCY4042A1 AT 1400 NOM CFM (COOLING PERFORMANCE AT INDOOR DRY BULB TEMPERATURES)

OD AMB	ID WB	TOT CAP	SENS CAP AT ENTERING DB TEMP				TOTAL KW
			72	75	78	80	
85	59	40.1	33.5	37.6	40.1	40.1	3.1
	63	41.8	27.3	31.4	35.5	38.3	3.1
	67	45.1	21.5	25.7	29.8	32.5	3.2
	71	48.7	15.8	19.9	24.1	26.8	3.2
95	59	37.5	32.3	36.5	37.5	37.5	3.4
	63	39.1	26.2	30.3	34.4	37.2	3.5
	67	42.2	20.4	24.6	28.7	31.5	3.5
	71	45.5	14.7	18.9	23.0	25.7	3.5
105	59	34.9	31.2	34.9	34.9	34.9	3.8
	63	36.4	25.0	29.2	33.3	36.1	3.8
	67	39.2	19.4	23.5	27.6	30.4	3.9
	71	42.4	13.6	17.7	21.9	24.6	3.9
115	59	32.3	30.1	32.3	32.3	32.3	4.1
	63	33.7	24.0	28.1	32.2	33.7	4.1
	67	36.3	18.3	22.4	26.6	29.3	4.2
	71	39.2	12.6	16.7	20.8	23.6	4.2

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW

	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1225	0.97	0.98
HIGH	1575	1.03	1.02

ARI RATING FOR COOLING

CFM	CAPACITY (A) TEST	SEER	EER
1370	42000	14.25	12.00

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4048A1/3 AT 1600 NOM CFM (COOLING PERFORMANCE AT INDOOR DRY BULB TEMPERATURES)

OD AMB	ID WB	TOT CAP	SENS CAP AT ENTERING DB TEMP				TOTAL KW
			72	75	78	80	
85	59	45.5	38.4	43.1	45.5	45.5	3.5
	63	47.5	31.2	35.9	40.7	43.9	3.6
	67	51.2	24.6	29.3	34.1	37.3	3.6
	71	55.2	18.0	22.8	27.5	30.7	3.6
95	59	42.5	37.0	41.8	42.5	42.5	3.9
	63	44.3	29.9	34.6	39.4	42.6	4.0
	67	47.7	23.3	28.1	32.8	36.0	4.0
	71	51.6	16.7	21.5	26.2	29.4	4.0
105	59	39.5	35.7	39.5	39.5	39.5	4.3
	63	41.1	28.6	33.3	38.1	41.1	4.4
	67	44.3	22.0	26.8	31.5	34.7	4.4
	71	47.9	15.5	20.2	25.0	28.2	4.4
115	59	36.4	34.3	36.4	36.4	36.4	4.7
	63	38.0	27.3	32.1	36.8	38.0	4.7
	67	40.9	20.8	25.5	30.3	33.5	4.8
	71	44.2	14.2	19.0	23.8	26.9	4.8

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW

	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1400	0.97	0.98
HIGH	1800	1.03	1.02

ARI RATING FOR COOLING

CFM	CAPACITY (A) TEST	SEER	EER
1470	47000	14.00	11.75

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4060A1/3 AT 2000 NOM CFM (COOLING PERFORMANCE AT INDOOR DRY BULB TEMPERATURES)

OD AMB	ID WB	TOT CAP	SENS CAP AT ENTERING DB TEMP				TOTAL KW
			72	75	78	80	
85	59	55.9	48.3	54.4	55.9	55.9	4.5
	63	58.3	39.0	45.2	51.4	55.5	4.5
	67	62.8	30.4	36.6	42.8	47.0	4.6
	71	67.8	21.8	28.0	34.2	38.3	4.6
95	59	52.5	46.8	52.5	52.5	52.5	4.9
	63	54.8	37.6	43.7	49.9	54.1	5.0
	67	59.0	29.0	35.2	41.4	45.5	5.0
	71	63.7	20.4	26.6	32.8	36.9	5.0
105	59	49.2	45.3	49.2	49.2	49.2	5.4
	63	51.3	36.2	42.3	48.5	51.3	5.4
	67	55.3	27.6	33.8	40.0	44.1	5.5
	71	59.7	19.0	25.3	31.4	35.6	5.5
115	59	45.8	43.8	45.8	45.8	45.8	5.9
	63	47.8	34.8	40.9	47.1	47.8	5.9
	67	51.5	26.2	32.4	38.6	42.8	6.0
	71	55.6	17.7	23.9	30.1	34.2	6.0

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW

	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1750	0.97	0.98
HIGH	2250	1.03	1.02

ARI RATING FOR COOLING

CFM	CAPACITY (A) TEST	SEER	EER
1743	57500	14.00	11.50

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

Performance Data Heating

4DCY4024A1 AT 800 NOM CFM (HEATING PERFORMANCE AT INDOOR DRY BULB TEMPERATURE)

OD AMB	TOTAL CAPACITY MBH				TOTAL POWER IN KILOWATTS			
	60	70	75	80	60	70	75	80
2	6.4	6.3	6.2	6.1	1.2	1.3	1.3	1.3
7	8.2	8.1	8.0	7.9	1.2	1.3	1.4	1.4
12	10.1	9.9	9.8	9.7	1.3	1.4	1.4	1.5
17	11.9	11.7	11.6	11.5	1.4	1.4	1.5	1.5
22	12.4	12.2	12.1	11.9	1.4	1.5	1.5	1.6
27	12.9	12.6	12.5	12.4	1.5	1.5	1.6	1.6
32	13.3	13.1	12.9	12.8	1.5	1.6	1.7	1.7
37	15.2	14.9	14.7	14.6	1.6	1.7	1.7	1.8
42	19.1	18.8	18.6	18.4	1.6	1.7	1.8	1.8
47	23.1	22.6	22.4	22.2	1.7	1.8	1.8	1.9
52	24.9	24.4	24.2	24.0	1.7	1.8	1.9	2.0
57	26.8	26.3	26.0	25.8	1.8	1.9	2.0	2.0
62	28.6	28.1	27.8	27.5	1.8	2.0	2.0	2.1
67	30.5	29.9	29.6	29.3	1.9	2.0	2.1	2.1
72	32.3	31.7	31.4	31.1	1.9	2.1	2.1	2.2

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	700	0.987	0.975
HIGH	900	1.011	1.025

ARI RATING FOR HEATING					
CFM	CAPACITY 47	COP 47	CAPACITY 17	COP 17	HSPF
758	22400	3.70	11600	2.38	8.00

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4030A1 AT 1000 NOM CFM (HEATING PERFORMANCE AT INDOOR DRY BULB TEMPERATURE)

OD AMB	TOTAL CAPACITY MBH				TOTAL POWER IN KILOWATTS			
	60	70	75	80	60	70	75	80
2	9.5	9.3	9.2	9.2	1.6	1.7	1.8	1.8
7	11.7	11.5	11.4	11.3	1.6	1.8	1.8	1.9
12	13.9	13.6	13.5	13.4	1.7	1.8	1.9	1.9
17	16.1	15.8	15.6	15.5	1.7	1.8	1.9	2.0
22	17.1	16.8	16.6	16.5	1.8	1.9	1.9	2.0
27	18.1	17.8	17.6	17.5	1.8	1.9	2.0	2.1
32	19.2	18.8	18.6	18.5	1.9	2.0	2.0	2.1
37	21.4	21.0	20.8	20.6	1.9	2.0	2.1	2.1
42	25.3	24.8	24.6	24.4	2.0	2.1	2.1	2.2
47	29.2	28.7	28.4	28.1	2.0	2.1	2.2	2.3
52	31.4	30.8	30.5	30.3	2.1	2.2	2.2	2.3
57	33.6	33.0	32.7	32.4	2.1	2.2	2.3	2.4
62	35.8	35.1	34.8	34.5	2.1	2.3	2.3	2.4
67	38.0	37.3	36.9	36.6	2.2	2.3	2.4	2.5
72	40.2	39.5	39.1	38.7	2.2	2.4	2.4	2.5

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	875	0.987	0.975
HIGH	1125	1.011	1.025

ARI RATING FOR HEATING					
CFM	CAPACITY 47	COP 47	CAPACITY 17	COP 17	HSPF
880	28000	3.90	15400	2.48	8.00

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4036A1/3 AT 1200 NOM CFM (HEATING PERFORMANCE AT INDOOR DRY BULB TEMPERATURE)

OD AMB	TOTAL CAPACITY MBH				TOTAL POWER IN KILOWATTS			
	60	70	75	80	60	70	75	80
2	13.9	13.6	13.5	13.4	2.3	2.4	2.5	2.5
7	16.3	16.0	15.8	15.7	2.3	2.5	2.5	2.6
12	18.7	18.3	18.1	18.0	2.4	2.5	2.6	2.7
17	21.0	20.6	20.4	20.3	2.4	2.6	2.6	2.7
22	21.3	20.9	20.7	20.5	2.4	2.6	2.7	2.7
27	21.5	21.1	20.9	20.7	2.4	2.6	2.7	2.7
32	21.7	21.3	21.1	20.9	2.4	2.6	2.7	2.7
37	24.1	23.7	23.4	23.2	2.5	2.6	2.7	2.8
42	29.7	29.2	28.9	28.6	2.6	2.8	2.9	2.9
47	35.3	34.7	34.3	34.0	2.7	2.9	3.0	3.1
52	37.7	37.0	36.6	36.3	2.8	3.0	3.0	3.1
57	40.1	39.3	39.0	38.6	2.8	3.0	3.1	3.2
62	42.5	41.7	41.3	40.9	2.9	3.1	3.2	3.3
67	44.9	44.0	43.6	43.2	2.9	3.1	3.2	3.3
72	47.2	46.4	45.9	45.5	3.0	3.2	3.3	3.4

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1050	0.987	0.975
HIGH	1350	1.011	1.025

ARI RATING FOR HEATING					
CFM	CAPACITY 47	COP 47	CAPACITY 17	COP 17	HSPF
1187	34600	3.50	20600	2.36	8.00

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

Performance Data Heating

4DCY4042A1 AT 1400 NOM CFM (HEATING PERFORMANCE AT INDOOR DRY BULB TEMPERATURE)

OD AMB	TOTAL CAPACITY MBH				TOTAL POWER IN KILOWATTS			
	60	70	75	80	60	70	75	80
2	16.0	15.7	15.6	15.4	2.8	3.0	3.1	3.2
7	18.7	18.4	18.2	18.0	2.8	3.0	3.1	3.2
12	21.4	21.0	20.8	20.6	2.9	3.0	3.1	3.2
17	24.1	23.7	23.5	23.2	2.9	3.1	3.2	3.3
22	25.5	25.1	24.8	24.6	2.9	3.1	3.2	3.3
27	26.9	26.4	26.2	25.9	2.9	3.1	3.2	3.3
32	28.3	27.8	27.5	27.3	2.9	3.1	3.2	3.3
37	31.0	30.4	30.1	29.9	2.9	3.1	3.2	3.3
42	35.7	35.1	34.7	34.4	3.0	3.2	3.3	3.4
47	40.4	39.7	39.3	38.9	3.0	3.2	3.3	3.4
52	43.1	42.3	41.9	41.5	3.1	3.3	3.3	3.4
57	45.8	45.0	44.5	44.1	3.1	3.3	3.4	3.5
62	48.5	47.6	47.2	46.7	3.1	3.3	3.4	3.5
67	51.3	50.3	49.8	49.3	3.1	3.3	3.4	3.5
72	54.0	53.0	52.4	52.0	3.2	3.4	3.5	3.6

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1225	0.987	0.975
HIGH	1575	1.011	1.025

ARI RATING FOR HEATING					
CFM	CAPACITY 47	COP 47	CAPACITY 17	COP 17	HSPF
1370	39500	3.60	23600	2.26	8.00

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4048A1/3 AT 1600 NOM CFM (HEATING PERFORMANCE AT INDOOR DRY BULB TEMPERATURE)

OD AMB	TOTAL CAPACITY MBH				TOTAL POWER IN KILOWATTS			
	60	70	75	80	60	70	75	80
2	18.1	17.7	17.6	17.4	3.1	3.2	3.3	3.4
7	21.3	20.9	20.7	20.5	3.1	3.3	3.4	3.5
12	24.5	24.1	23.8	23.6	3.2	3.4	3.5	3.6
17	27.7	27.2	27.0	26.7	3.2	3.4	3.5	3.7
22	30.8	30.2	29.9	29.7	3.3	3.5	3.6	3.7
27	33.9	33.2	32.9	32.6	3.4	3.6	3.7	3.8
32	36.9	36.3	35.9	35.6	3.4	3.6	3.7	3.9
37	40.2	39.4	39.0	38.7	3.5	3.7	3.8	3.9
42	43.6	42.8	42.4	42.0	3.5	3.8	3.9	4.0
47	47.1	46.2	45.8	45.4	3.6	3.8	4.0	4.1
52	50.3	49.4	48.9	48.5	3.7	3.9	4.0	4.1
57	53.6	52.6	52.0	51.6	3.7	4.0	4.1	4.2
62	56.8	55.7	55.2	54.7	3.8	4.0	4.2	4.3
67	60.0	58.9	58.3	57.8	3.9	4.1	4.2	4.3
72	63.2	62.1	61.4	60.9	3.9	4.2	4.3	4.4

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1400	0.987	0.975
HIGH	1800	1.011	1.025

ARI RATING FOR HEATING					
CFM	CAPACITY 47	COP 47	CAPACITY 17	COP 17	HSPF
1470	45500	3.50	26800	2.30	8.00

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

4DCY4060A1/3 AT 2000 NOM CFM (HEATING PERFORMANCE AT INDOOR DRY BULB TEMPERATURE)

OD AMB	TOTAL CAPACITY MBH				TOTAL POWER IN KILOWATTS			
	60	70	75	80	60	70	75	80
2	27.3	26.8	26.5	26.3	3.9	4.1	4.3	4.4
7	30.9	30.3	30.0	29.7	4.0	4.2	4.3	4.5
12	34.5	33.8	33.5	33.2	4.0	4.3	4.4	4.6
17	38.1	37.4	37.0	36.7	4.1	4.4	4.5	4.6
22	38.9	38.2	37.8	37.5	4.1	4.4	4.5	4.7
27	39.7	39.0	38.6	38.3	4.2	4.4	4.6	4.7
32	40.6	39.8	39.4	39.1	4.2	4.4	4.6	4.7
37	44.2	43.3	42.9	42.5	4.3	4.5	4.7	4.8
42	51.9	50.9	50.4	50.0	4.4	4.7	4.8	5.0
47	59.6	58.5	57.9	57.4	4.6	4.9	5.0	5.1
52	63.2	62.0	61.4	60.9	4.6	4.9	5.1	5.2
57	66.8	65.6	64.9	64.3	4.7	5.0	5.2	5.3
62	70.4	69.1	68.4	67.8	4.8	5.1	5.2	5.4
67	74.0	72.6	71.9	71.2	4.9	5.2	5.3	5.5
72	77.6	76.1	75.4	74.7	4.9	5.2	5.4	5.6

USE THE FOLLOWING FACTORS TO COMPENSATE FOR DIFFERENT AIR FLOW			
	AIR FLOW RATE, CFM	CAPACITY MULTIPLIER	TOTAL POWER MULTIPLIER
LOW	1750	0.987	0.975
HIGH	2250	1.011	1.025

ARI RATING FOR HEATING					
CFM	CAPACITY 47	COP 47	CAPACITY 17	COP 17	HSPF
1743	57000	3.50	36400	2.48	8.00

ARI Standard Capacity Rating Conditions

ARI STANDARD 210/240 RATING CONDITIONS — (A) Cooling 80°F DB, 67°F WB air entering indoor coil, 95°F DB air entering outdoor coil. (B) High Temperature Heating 47°F DB, 43°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (C) Low Temperature Heating 17°F DB, 15°F WB air entering outdoor coil, 70°F DB air entering indoor coil. (D) Rated indoor airflow for heating is the same as for cooling.

Indoor Blower Performance

Indoor Fan Performance 4DCY4024A

Horizontal Airflow

4DCY4024A-HOR	DIPSWITCH SETTINGS				External Static Pressure (in. wg)												
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
350 CFM/TON	OFF	OFF	OFF	ON	Watts	52	66	89	115	140	164	186	206	229	259	-	
					CFM	706	716	727	733	731	719	700	679	662	659	-	
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	72	94	120	148	177	207	233	254	267	290	-	
					CFM	786	793	805	813	813	806	793	780	778	799	-	
450 CFM/TON	OFF	OFF	ON	OFF	Watts	80	99	125	153	182	211	243	284	342	-	-	
					CFM	860	862	877	892	903	904	897	884	869	-	-	

Down Airflow

4DCY4024A-DOWN	DIPSWITCH SETTINGS				External Static Pressure (in. wg)												
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
350 CFM/TON	OFF	OFF	OFF	ON	Watts	35	70	90	108	131	160	188	204	225	250	-	
					CFM	695	729	734	728	721	715	705	679	680	685	-	
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	79	87	105	129	155	180	206	232	264	306	-	
					CFM	846	807	802	810	816	813	803	794	800	846	-	
450 CFM/TON	OFF	OFF	ON	OFF	Watts	86	102	127	156	185	213	242	275	319	-	-	
					CFM	884	870	882	899	909	907	895	886	898	-	-	

Indoor Fan Performance 4DCY4030A

Horizontal Airflow

4DCY4030A-HOR	DIPSWITCH SETTINGS				External Static Pressure (in. wg)												
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
350 CFM/TON	OFF	OFF	OFF	ON	Watts	-	112	155	176	199	231	270	299	289	197	-	
					CFM	-	867	905	904	899	904	914	907	840	650	-	
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	-	157	192	222	249	276	306	343	389	448	-	
					CFM	-	997	1011	1012	1009	1006	1006	1006	1001	982	-	
450 CFM/TON	OFF	OFF	ON	OFF	Watts	-	213	252	285	317	351	382	401	396	-	-	
					CFM	-	1125	1135	1132	1133	1138	1138	1110	1017	-	-	

Down Airflow

4DCY4030A-DOWN	DIPSWITCH SETTINGS				External Static Pressure (in. wg)												
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
350 CFM/TON	OFF	OFF	OFF	ON	Watts	-	126	152	182	211	237	263	292	333	397	497	
					CFM	-	883	900	911	911	901	883	863	849	854	890	
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	-	158	196	224	251	283	318	344	345	295	162	
					CFM	-	987	1004	1006	1004	1001	994	977	936	851	697	
450 CFM/TON	OFF	OFF	ON	OFF	Watts	-	218	254	288	321	354	390	431	480	-	-	
					CFM	-	1118	1128	1132	1131	1127	1127	1142	1183	-	-	

*Factory Default Setting

Auxiliary Heating Airflow, horizontal or downflow from .2 to .6" wg.

4DCY4024A1064				
Switch Settings		Selection	Nominal Airflow	
			Low Stage	High Stage
7-OFF	8-OFF	A	600	850
7-ON	8-OFF	B	625	900
7-OFF	8-ON	C	650	925
7-ON	8-ON	D	700	975

4DCY4030A				
Switch Settings		Selection	Nominal Airflow	
			Low Stage	High Stage
7-OFF	8-OFF	A	725	1000
7-ON	8-OFF	B	775	1075
7-OFF	8-ON	C	850	1150
7-ON	8-ON	D	925	1250

Indoor Blower Performance

Indoor Fan Performance 4DCY4036A

Horizontal Airflow

4DCY4036A-HOR	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	162	173	197	226	256	285	313	343	360	-	-
					CFM	1058	1062	1063	1063	1062	1060	1057	1053	1010	-	-
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	179	230	265	296	329	366	403	431	436	-	-
					CFM	1179	1196	1204	1206	1205	1203	1199	1194	1185	-	-
450 CFM/TON	OFF	OFF	ON	OFF	Watts	318	336	365	399	435	469	502	533	-	-	-
					CFM	1390	1376	1370	1366	1361	1354	1349	1351	-	-	-

Down Airflow

4DCY4036A-DOWN	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	169	182	210	243	273	301	331	370	433	-	-
					CFM	1025	1062	1068	1063	1060	1061	1064	1055	1015	-	-
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	225	253	283	315	348	381	414	449	484	-	-
					CFM	1187	1201	1203	1201	1198	1197	1194	1184	1157	-	-
450 CFM/TON	OFF	OFF	ON	OFF	Watts	339	357	390	424	455	483	516	571	-	-	-
					CFM	1391	1377	1377	1375	1366	1352	1344	1360	-	-	-

Indoor Fan Performance 4DCY4042A

Horizontal Airflow

4DCY4042A-HOR	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	-	160	185	214	245	277	308	339	368	396	423
					CFM	-	1206	1211	1213	1215	1215	1214	1212	1208	1201	1190
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	-	231	261	292	325	359	394	431	467	503	536
					CFM	-	1389	1398	1405	1409	1410	1408	1403	1399	1396	1399
450 CFM/TON	OFF	OFF	ON	OFF	Watts	-	326	362	393	421	450	482	517	556	597	-
					CFM	-	1582	1592	1593	1587	1577	1566	1557	1553	1556	-

Down Airflow

4DCY4042A-DOWN	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	-	176	203	232	262	294	325	357	388	417	443
					CFM	-	1207	1214	1217	1216	1213	1208	1201	1193	1185	1177
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	-	253	290	323	355	386	420	455	491	526	558
					CFM	-	1405	1411	1413	1412	1407	1399	1389	1377	1366	1357
450 CFM/TON	OFF	OFF	ON	OFF	Watts	-	367	379	409	446	485	522	556	591	633	-
					CFM	-	1599	1577	1570	1569	1566	1560	1550	1537	1528	-

*Factory Default Setting

Auxiliary Heating Airflow, horizontal or downflow from .2 to .6" wg.

4DCY4036A				
Switch Settings		Selection	Nominal Airflow	
			Low Stage	High Stage
7-OFF	8-OFF	A	725	1000
7-ON	8-OFF	B	775	1075
7-OFF	8-ON	C	850	1150
7-ON	8-ON	D	925	1250

4DCY4042A				
Switch Settings		Selection	Nominal Airflow	
			Low Stage	High Stage
7-OFF	8-OFF	A	1075	1375
7-ON	8-OFF	B	1100	1450
7-OFF	8-ON	C	1150	1500
7-ON	8-ON	D	1200	1575

Indoor Blower Performance

Indoor Fan Performance 4DCY4048A

Horizontal Airflow

4DCY4048A-HOR	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	187	232	264	291	318	347	379	413	446	472	-
					CFM	1355	1387	1396	1392	1382	1370	1360	1351	1341	1326	-
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	315	324	352	389	428	464	498	529	563	606	-
					CFM	1603	1581	1577	1580	1583	1583	1577	1567	1558	1556	-
450 CFM/TON	OFF	OFF	ON	OFF	Watts	301	431	507	552	584	615	651	694	739	779	-
					CFM	1752	1794	1812	1816	1812	1806	1800	1797	1793	1785	-

Down Airflow

4DCY4048A-DOWN	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	208	254	284	312	343	379	414	437	460	490	-
					CFM	1337	1393	1398	1388	1383	1390	1399	1384	1380	1370	-
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	302	349	386	423	465	509	552	583	599	628	-
					CFM	1574	1580	1585	1589	1594	1598	1601	1597	1584	1556	-
450 CFM/TON	OFF	OFF	ON	OFF	Watts	501	523	555	592	631	672	714	760	800	845	-
					CFM	1847	1823	1817	1818	1820	1819	1817	1820	1815	1810	-

Indoor Fan Performance 4DCY4060A

Horizontal Airflow

4DCY4060A-HOR	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	394	427	464	504	548	591	633	668	-	-	-
					CFM	1673	1772	1799	1793	1779	1771	1767	1756	-	-	-
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	695	642	660	710	764	811	849	893	966	1108	-
					CFM	2054	2036	2031	2032	2033	2031	2023	2012	2002	2000	-

Down Airflow

4DCY4060A-DOWN	DIPSWITCH SETTINGS				External Static Pressure (in. wg)											
AIRFLOW SETTING	1	2	3	4		0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
350 CFM/TON	OFF	OFF	OFF	ON	Watts	443	461	493	532	571	607	642	680	-	-	-
					CFM	1796	1741	1726	1725	1722	1712	1698	1692	-	-	-
400 CFM/TON*	OFF	OFF	OFF	OFF	Watts	740	697	715	763	819	866	892	894	872	835	-
					CFM	2010	1987	1979	1977	1976	1969	1950	1913	1852	1759	-

*Factory Default Setting

Auxiliary Heating Airflow, horizontal or downflow from .2 to .6" wg.



4DCY4048A*096				
Switch Settings		Selection	Nominal Airflow	
			Low Stage	High Stage
7-OFF	8-OFF	A	1075	1375
7-ON	8-OFF	B	1100	1450
7-OFF	8-ON	C	1150	1500
7-ON	8-ON	D	1200	1575

* can be 1 or 3

4DCY4060A*120				
Switch Settings		Selection	Nominal Airflow	
			Low Stage	High Stage
7-OFF	8-OFF	A	1375	1800
7-ON	8-OFF	B	1450	1900
7-OFF	8-ON	C	1525	1975
7-ON	8-ON	D	1575	2075

Typical Field Wiring


4DCY FIELD WIRING DIAGRAM




NOTES:

1. FUSED DISCONNECT SIZE, POWER WIRING AND GROUNDING OF EQUIPMENT MUST COMPLY WITH CODES.
2. BE SURE POWER SUPPLY AGREES WITH EQUIPMENT NAMEPLATE.
3. LOW VOLTAGE WIRING TO BE 18 AWG MINIMUM CONDUCTOR.
4. SEE UNIT DIAGRAM FOR ELECTRICAL CONNECTION DETAILS.
5. WHEN THE BAYECON101A, 102A, 200A OR 201A ECONOMIZER IS INSTALLED, THE BAYLAY004 RELAY ACCESSORY KIT IS REQUIRED TO INTERFACE THE ECONOMIZER TO THE HEAT PUMP FOR PROPER SYSTEM OPERATION.
6. THE OUTDOOR SENSOR SHOULD BE LOCATED IN AN AREA WHICH WILL PROVIDE A REPRESENTATIVE OUTDOOR TEMPERATURE.
7. A FIELD INSTALLED JUMPER WIRE MUST BE PLACED BETWEEN W1 AND W2/X2 AT THE UNIT FOR COMFORT CONTROLS *CONT 802A AND 803A TO PROPERLY FUNCTION.

Typical Wiring




Typical Wiring




Optional Equipment

BAYCURB050A Full Perimeter Roof Mounting Curb for *****024-036A



The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.




	SERVICE CLEARANCE DIMENSIONS			
	A	B	C	D
WC*/TC*	42.00	36.00	12.00**	24.00
DC*/YC*	42.00	36.00	12.00**	36.00


** 42.00 WITH ECONOMIZER WITH 25% FRESH AIR ACCESSORY

Optional Equipment

BAYCURB051A Full Perimeter Roof Mounting Curb for *****042-060A



The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.




	SERVICE CLEARANCE DIMENSIONS			
	A	B	C	D
WC*/TC*	42.00	36.00	12.00**	24.00
DC*/YC*	42.00	36.00	12.00**	36.00


** 42.00 WITH ECONOMIZER WITH 25% FRESH AIR ACCESSORY

Optional Equipment

**BAYFLTR101, 201B, 1" - 2" Filter Rack
(Mounts in Filter/Coil Section)**




**BAYACCDOR1A & BAYACCDOR2A Hinged Filter Access Door
Replaces Filter/Coil Access Panel**



The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.

Optional Equipment


BAYECON101,102A Down Discharge Economizer and Rain Hood (Mounts Over Horizontal Return Air Opening)



Economizer	Unit Application Models	A
BAYECON101A	2/4YC, WC3018-036 4TC*3018-036 4W/T/Y/DCY4024-060	20.125"
BAYECON102A	2/4YC, WC3042-060 4TC*3042-060 4W/T/Y/DCY4024-060	24.375"

BAYECON200,201A Horizontal Economizer and Rain Hood

The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.




Economizer	A	B	C	D	E
BAYECON200AA	22"	20"	16 7/8"	15 11/16"	11 11/16"
BAYECON201AA	26"	22 21/32"	19"	17 11/16"	14 11/16"

Optional Equipment


BAYOSAH001,002A, 25% Outside Air Damper (Replaces Filter/Coil Access Panel)

The drawings on this page are prepared by the manufacturer in order to provide detail regarding job layout only. These drawings are not intended to be used as a basis to construct, build or modify the items depicted in the drawings. The manufacturer is not responsible for the unauthorized use of these drawings and expressly disclaims any liability for damages resulting from such unauthorized use.








Manual Fresh Air Model	Unit Application Models	A	B	C	D
BAYOSAH001	2/4YC,WC3018-036 4TC*3018-036 4W/T/Y/DCY4024-036 4W/Y/DCZ6036	22 7/16"	20 11/16"	12 3/8"	9 3/16"
BAYOSAH002	2/4YC,WC3042-060 4TC*3042-060 4W/T/Y/DCY4042-060 4W/Y/DCZ6048-060	25 3/16"	20 11/16"	12 3/8"	9 3/16"

BAYDMPR101,102A, 25% Motorized Outside Air Damper (Mounts Over Horizontal Return Air Opening)




	Unit Application Models	A	B	C	D	E
BAYDMPR101A	2/4YC,WC3018-036 4TC3018-036 4W/T/Y/DCY4024-036 4W/Y/DCZ6036	15 13/16"	11 13/16"	10 1/4"	11 1/2"	12 1/4"
BAYDMPR102A	2/4YC,WC3042-060 4TC3042-060 4W/T/Y/DCY4042-060 4W/Y/DCZ6048-060	18 3/16"	15 1/8"	10 1/4"	11 1/2"	12 1/4"

Dimensional Data



4DCY4024A through 4DCY4036A (1 of 3)


Dimensional Data



RECOMMENDED SERVICE CLEARANCE MM/IN.		
		WITH ECONOMIZER
BACK SIDE	304.8 [12]	762.0 [30]
LEFT SIDE	762.0 [30]	914.4 [36]
RIGHT SIDE	914.4 [36]	-
FRONT SIDE	1066.8 [42]	-




BOTTOM DUCT OPENINGS

CLEARANCE TO COMBUSTIBLE MATERIAL MM/IN.	
BOTTOM	0
BACK SIDE	25.4 [1]
LEFT SIDE	152.4 [6]
RIGHT SIDE	304.8 [12]
FRONT SIDE	304.8 [12]
TOP	914.4 [36]



4DCY4024A through 4DCY4036A (2 of 3)

Dimensional Data




SECTION X-X
TYPICAL (8) SIDES OF SIDEFLOW DUCT OPENINGS

MODEL	HEIGHT MM/IN.	FLUE HOOD W/BRKT MM/IN.	APPROX. CORNER WEIGHT - KG/LBS				SHIPPING WEIGHT KG/LBS	TOTAL UNIT WEIGHT KG/LBS	CENTER OF GRAVITY MM/IN.	
	A		W1	W2	W3	W4			B	C
4YCY4024 (064)	903.29 [35-9/16]	-	59.0 [130]	37.2 [82]	31.3 [69]	48.5 [107]	218.4 (481)	174.8 [385]	401.3 [15.8]	546.1 [21.5]
4YCY4030 (075)		-	59.0 [130]	37.2 [82]	31.3 [69]	48.5 [107]	218.4 (481)	174.8 [385]	401.3 [15.8]	546.1 [21.5]
4YCY4036/4YCY6036 (075)	949.99 [37-3/8]	117.86 [4-5/8]	60.3 [133]	36.3 [80]	30.4 [67]	50.3 [111]	221.6 (488)	178.0 [392]	388.6 [15.3]	558.8 [22.0]
4YCY4036/4YCY6036 (096)			61.2 [135]	36.7 [81]	30.8 [68]	51.3 [113]	223.8 (493)	180.1 [397]	388.6 [15.3]	558.8 [22.0]
4DCY4024 (064)	903.29 [35-9/16]	-	60.8 [134]	38.1 [84]	31.3 [69]	48.5 [107]	218.4 (481)	174.8 [385]	398.8 [15.7]	546.1 [21.5]
4DCY4030 (075)		-	60.8 [134]	38.1 [84]	31.3 [69]	48.5 [107]	218.4 (481)	174.8 [385]	398.8 [15.7]	546.1 [21.5]
4DCY4036/4DCY6036 (075)	949.99 [37-3/8]	117.86 [4-5/8]	62.1 [137]	37.2 [82]	30.4 [67]	50.3 [111]	221.6 (488)	178.0 [392]	386.1 [15.2]	558.8 [22.0]

4DCY4024A through 4DCY4036A (3 of 3)


Dimensional Data



4DCY4042A through 4DCY4060A (1 of 3)

Pub. No. 12-1254-08


Dimensional Data



RECOMMENDED SERVICE CLEARANCE MM/IN.		
		WITH O.A. DAMPER/ECON.
BACK SIDE	304.8 [12]	762.0 [30]
LEFT SIDE	914.4 [36]	1066.8 [42]
RIGHT SIDE	914.4 [36]	-
FRONT SIDE	1066.8 [42]	-


BOTTOM DUCT OPENINGS

CLEARANCE TO COMBUSTIBLE MATERIAL MM/IN.	
BOTTOM	0
BACK SIDE	25.4 [1]
LEFT SIDE	152.4 [6]
RIGHT SIDE	304.8 [12]
FRONT SIDE	304.8 [12]
TOP	914.4 [36]



4DCY4042A through 4DCY4060A (2 of 3)

Dimensional Data



MODEL	HEIGHT MM/IN.	APPROX. CORNER WEIGHT - KG/LBS				SHIPPING WEIGHT KG/LBS	TOTAL UNIT WEIGHT KG/LBS	CENTER OF GRAVITY MM/IN.	
	A	W1	W2	W3	W4			B	C
4YCY4042/048 (096)	949.33 [37-3/8]	75.3 [166]	50.3 [111]	45.4 [100]	67.6 [149]	296.5 [653]	238.1 [525]	444.5 [17.5]	698.5 [27.5]
4YCY4048 (120)		75.7 [167]	50.8 [112]	45.8 [101]	68.5 [151]	299.2 [659]	240.9 [531]	444.5 [17.5]	698.5 [27.5]
4YCY4060A1/A3 (120)	1050.93 [41-3/8]	82.1 [181]	46.3 [102]	43.1 [95]	76.7 [169]	306.9 [676]	248.6 [548]	401.3 [15.8]	711.2 [28.0]
4DCY4042/048 (096)	949.33 [37-3/8]	77.1 [170]	51.3 [113]	45.4 [100]	67.6 [149]	296.5 [653]	238.4 [525]	442.0 [17.4]	698.5 [27.5]
4DCY4060 (120)	1050.93 [41-3/8]	83.9 [185]	47.2 [104]	43.1 [95]	76.7 [169]	306.9 [676]	248.8 [548]	398.8 [15.7]	711.2 [28.0]
4YCY4060A1/A3/A4 (096)	1050.93 [41-3/8]	75.7 [167]	50.8 [112]	45.8 [101]	68.5 [151]	299.2 [659]	240.9 [531]	444.5 [17.5]	698.5 [27.5]
4YCY4060A1/A3/A4 (120)		81.6 [180]	46.3 [102]	42.2 [93]	73.5 [162]	301.6 [665]	243.6 [537]	419.1 [16.5]	706.1 [27.8]
4YCY4060A1/A3/A4 (120)	1050.93 [41-3/8]	82.1 [181]	46.3 [102]	43.1 [95]	76.7 [169]	306.9 [676]	248.6 [548]	401.3 [15.8]	711.2 [28.0]
4DCY4060 (096)	1050.93 [41-3/8]	81.6 [180]	46.3 [102]	42.2 [93]	73.5 [162]	301.6 [665]	243.6 [537]	419.1 [16.5]	706.1 [27.8]
4DCY4060 (120)	1050.93 [41-3/8]	83.9 [185]	47.2 [104]	43.1 [95]	75.7 [169]	306.9 [676]	248.8 [548]	398.8 [15.7]	711.2 [28.0]

4DCY4042A through 4DCY4060A (3 of 3)

Mechanical Specifications

General

All units shall be factory assembled, piped, internally wired and fully charged with refrigerant. All units shall be designed to operate at outdoor ambient temperatures as high as 115°F. Cooling capacities shall be rated in accordance with A.H.R.I. standards. The 4DCY4 heating/cooling unit design is UL certified to UL Standards 1995 and ANSI 221.47/CSA 2.3, specifically for outdoor applications using natural gas or propane. All units shall be designed for outdoor rooftop or ground level installation. Unit casing is constructed of heavy gauge, galvanized steel and painted with a weather-resistant powder paint.

Shipped for horizontal application, convertible to downflow.

Casings

All panels shall be heavy gauge steel, gasketed and insulated. Foil-faced insulation shall be in the heat exchanger section. Foil-faced insulation shall be in the evaporator section. Base pan shall be heavy gauge steel. **WEATHERGUARD™** exterior corrosion resistant screws shall be used for added resistance to rust and corrosion.

Controls

Refrigeration cycle controls shall include condenser fan, evaporator fan and compressor contactors. Compressors shall be equipped with a combination internal winding thermostat/current overload. Internal high pressure relief shall also be provided.

Refrigeration System

Compressors —

The **Duration™** compressor features internal over temperature and pressure protector, total dipped hermetic motor. Other features include: roto lock suction and discharge refrigeration connections, centrifugal oil pump, and low vibration and noise.

Evaporator Coil — Internally enhanced 3/8-inch OD seamless copper tubing mechanically bonded to aluminum fins, factory pressure and leak tested at 250 to 300 psig. All units have TXV to control refrigeration flow.

Condenser Coil —

The **Spine Fin™** condenser coil shall be continuously wrapped, corrosion resistant all aluminum with minimum brazed joints. This coil is 3/8 inch OD seamless aluminum tubing glued to a continuous aluminum fin. Coils are lab tested to withstand 2,000 pounds of pressure per square inch. The outdoor coil provides low airflow resistance and efficient heat transfer. The coil is protected on all four sides by louvered panels.

Indoor Air Fan — Direct-drive, forward-curved, centrifugal wheel in a Composite **Vortica®** Blower housing. Motor shall have thermal overload protection. Permanently lubricated motor bearings. Motor/blower assembly isolated from unit with rubber mounts.

Condenser Fan — Direct-drive, draw through propeller type. Weather-proofed permanent split capacitor fan motor shall have built-in thermal overload and permanently lubricated motor bearings.

Low Ambient — Standard refrigerant system operation down to 55°F. Low ambient accessory required for operation to 0°F ambient condition.

Gas-Fired Heating System — Models shall provide completely assembled, wired and piped gas fired heating systems within unit. Threaded gas connection on the unit.

Electronic Ignition System — Main burner is lit each time thermostat calls for gas heat. Flame sensor proves flame and keeps the main burners on. Should a loss of flame occur, the main valve closes and the spark recurs within 0.8 second. When thermostat is satisfied, main burner is extinguished.

Forced Combustion Blower — Insures flame stability under varying wind conditions. Gives higher combustion efficiency and location flexibility.

Heat Exchanger — stainless steel tubes. Free floating design.

Burners — Stainless steel. Multi-port inshot.

Accessories

(U.S. Domestic Models)

Roof Curb — The roof curb shall be designed to mate with the unit and provide support and complete weather-tight installation when properly installed. Curb shall ship knocked down for field assembly, and include wood nailer strips.

Modulating Economizer — This accessory shall be field installed and be composed of the following items: 0-100% fresh air damper, damper drive motor fixed dry bulb enthalpy control, and low voltage polarized plug for electrical connections. Solid state enthalpy or differential enthalpy control is optional. Economizer operations shall be controlled by the preset position of the enthalpy control. A barometric relief damper shall be standard with the economizer and provide a pressure operated damper that shall be gravity closing and prohibit entrance of outside air on equipment "off" cycle.

Manual Fresh Air Hood

Manual outside air provides a fixed outside air quantity from 0 to 25 percent. Includes hood and birdscreen.

Low Ambient Control

Control allows cycling of compressor under low ambient cooling conditions. Required for cooling operation to 0°F.

Propane Gas

Conversion Kit — For conversion from natural gas to LP gas.

